

Description

The MF006 reagent has been engineered to work quickly and is specifically designed for heavier waste streams. MF006 consists of a proprietary blend, incorporating both absorbent and adsorbent materials, resulting in low addition requirements to meet solids disposal criteria. MF006 is non-hazardous, non-toxic, chemically inert, non-dusty and absorbs very quickly. MF006 is ideal for solidifying semi-solids and sludges to pass the Paint Filter Test (PFT). Typical dosages for MF006 is 0.25 - 1% wt/wt.



Characteristics

Colour: White / Yellow

Moisture Content: 11-14%

Bulk Density (kg/L): 0.36 – 0.47

Bulk Density (lbs/ft³): 22.5 – 29.3

pH: 5.5 – 6.5

Benefits

- ✓ Immediately converts liquid/semi-solid waste streams to a solid (<30 min)
- ✓ Works effectively with bulk mixing applications
- ✓ Creates a dry, stackable solid for easy handling
- ✓ Can reduce weight and volume of waste material
- ✓ Helps waste pass paint filter criteria
- ✓ Key components are FDA approved
- ✓ Approved for use in clean fill applications in many jurisdictions
- ✓ Landfill friendly and does not biodegrade
- ✓ Suitable for manually mixing in small or large batches



**Reduce
Costs**



**Increase
Safety**



**Environment
Friendly**

The information and data contained herein are believed to be accurate and reliable. MetaFLO Technologies makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information. Product color on images may vary slightly.